RECESSED MOUNT ULTRA THINK LINEAR LIGHT

CAB201F

CAB201F is a recessed light made of extruded aluminum housing, capped with a flexible flush frosted lens.

This linear LED luminaire is designed to produce a uniform distribution of diffused light in wooden platforms. CAB201F has a narrow base and is suitable for closet, under cabinet, stair nosing and wall unit linear light designs. This channel comes in variable lengths up to 8 feet. *

Cab series are complemented with dimmable, energy-efficient, dot-free LED, producing high color rendering index lighting. The bright white LED light source with CCT options from 2200K to 6000K provides the environment with desired lighting that fits the design concept.

The lighting system can be conveniently controlled with wall remote, hand remote, and smart app options. CAB201F is a perfect fit for use in residential and commercial to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



ELECTRICAL

Input

BEYOND LIGHT

24 V - 2 W/ft

Power Supply

Class 2 Dimmable 20KHZ Lutron Hi-lume 0.1% Lutron 3-wire 100%-1%

Operating temp

- 31°F to + 113°F
- 35°C to + 45°C

CONTROL

Options

Combination of wireless wall touch keys, portable remotes, and mobile App

Range

Wireless controlling transmits RF in 30m range

Multi-zone

Individual and collective zone options for color and brightness control

Dimming

Brightness, color tuning, & light mode with memory saving options

PHYSICAL

Dimension

0.<mark>22in x 0.37i</mark>n - 5.5x9.3mm Up to 8 ft (2.5 m) length *

Finish

Dark Grey anodized finish *

Field

Indoor dry applications

Mounting

Recessed under cabinet or wooden platforms



LIGHT

LED type

Single White

CCT

3000K 3500K 4000K 4500K 5000K 5500K*

CRI

High CRI up to 97 *

Brighness

150 Lm/ft - 500 Lm/m *

Life time

50,000 hours

Warranty

5 years warranty

^{*} AVAILABLE FOR CUSTOM APPLICATIONS. VISIT ENOLIGHT.COM OR CONTACT SALESGENOLIGHT.COM +1 833 366 5444 FOR FURTHER DETAILS. DISCLAIMER: THE ACTUAL PRODUCT MAY VARY FROM THE IMAGES SHOWN. DUE TO DIFFERENCES IN MONITORS, COLOURS OF PRODUCTS MAY ALSO APPEAR DIFFERENT TO THOSE SHOWN. SPECIFICATION AND ILLUSTRATIONS PROVIDED FOR EACH PRODUCT IS TO BE USED AS A GENERAL GUIDE ONLY. COPYRIGHT © 2017-2019 ENOLIGHT LTD. ALL RIGHTS RESERVED.