

RECESSED MOUNT DRYWALL OUTER CORNER LINEAR LIGHT


SPARK SERIES **SPK5315F**

SPK5315F is a recessed linear profile made of extruded aluminum housing with a protective silver anodized finish, capped with a flush frosted lens.

This linear luminaire is designed to produce a uniform distribution of diffused light in drywall platforms. SPK5315F is suitable for outside corners and comes in variable lengths up to 8 feet.*

Spark series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. SPK5315F is a perfect fit for use in residential and commercial spaces for wet and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



ELECTRICAL

WATTAGE

2.4W/ft. 5W/ft 24 Volt DC input

OPERATING TEMP

- -31°F to +113°F
- -35°C to +45°C

CERTIFICATION

U.S./Canada UL approved Type IC Recessed



CONTROL

DIMMING MODE

Class 2 Flicker-Free Dimmable, DMX Tunable, Non-Dimmable

WALL KEYPAD

Dimmer switch, Multi-zone DMX dim and tuning touch key with smart mobile App

PHYSICAL

DIMENSION

2.08 in x 0.91 in, 53x23mm Up to 8ft length, 0.27 lb/ft

Silver anodized, Black matte, White matte '

FIELD

Recessed in wet or dry outside corners



50K

LIGHT

LED TYPE

Single white, Tunable white, RGBW, Circadian Rhythm

EFFICACY

100 Lm/W, Max 400 Lm/ft *

LIFESPAN

50,000 hours

WARRANTY

5 years warranty

SP	K5	31	5F

Drywall Outside Corner Linear Light

8F

1FT-8FT 1' to 8' Custom length up to 8'

200 200lm/ft 2.4W/ft 400 400lm/ft 5W/ft

200

BM Black Matte

SA

Silver Anodized WM White Matte

30K

27K 2700K Incandescent 90CRI 3000K Warm Halogen 90CRI 30K 35K 3500K Neutral White 90CRI 40K 4000K Cool White 90CRI 5000K Daylight White 90CRI

2700K-6500 Tunable 90CRI 27T RGBW RGB and 6500K White 90CRI CR Circadian Rhythm 97R9 98CRI

JT

JT Tr JX DI

-IN No JD DALI Dimmable

iac	Phase Dimming	F2	Dry Fiel
ИX	Multi-Channel	F5	Wet Fiel
on-l	Dimmable		

F2

^{*} Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details. Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.