



SPK8115F is a recessed linear profile made of extruded aluminum housing, capped with one inch wide flat frosted lens.

This linear luminaire is designed to produce a uniform distribution of diffused light in drywall platforms. SPK8115F is suitable for wall and ceiling linear light designs and comes in variable lengths up to 18 feet.*

Spark series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. SPK8115F is a perfect fit for use in residential and commercial spaces for wet and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



SPECIFICATIONS

ELECTRICAL

WATTAGE

2.4W/ft, 5W/ft, 10W/ft
24 Volt DC input

OPERATING TEMP

-31°F to +113°F
-35°C to +45°C

CERTIFICATION

U.S./Canada UL approved
Type IC Recessed



CONTROL

DIMMING MODE

Class 2 Flicker-Free
Dimmable, DMX Tunable,
Non-Dimmable

WALL KEYPAD

Dimmer switch, Multi-zone
DMX dim and tuning touch
key with smart mobile App

PHYSICAL

DIMENSION

3.2 in x 0.64 in, 81x15mm
Up to 18ft length, 0.36 lb/ft

FINISH

Silver anodized, Black matte,
White matte *

FIELD

Recessed in wet or dry
ceiling and wall areas



LIGHT

LED TYPE

Single white, Tunable white,
RGBW, Circadian Rhythm

EFFICACY

100 Lm/W, Max 800 Lm/ft *

LIFESPAN

50,000 hours

WARRANTY

5 years warranty

SPK8115F	12F	400	MF	30K	JT	F2
1 Inch Drywall Linear LED Light	1FT-18FT 1' to 18' Custom length up to 18'	200 200lm/ft 2.4W/ft 400 400lm/ft 5W/ft 800 800lm/ft 10W/ft	SA Silver Anodized BM Black Matte WM White Matte MF Mill Finish	27K 2700K Incandescent 90CRI 30K 3000K Warm Halogen 90CRI 35K 3500K Neutral White 90CRI 40K 4000K Cool White 90CRI 50K 5000K Daylight White 90CRI 27T 2700K-6500 Tunable 90CRI RGBW RGB and 6500K White 90CRI CR Circadian Rhythm 97R9 98CRI	JT Triac Phase Dimming JX DMX Multi-Channel JN Non-Dimmable JD DALI Dimmable	F2 Dry Field F5 Wet Field

* Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details.

Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.