
2.01

Rope lock system

<u> Ennuré</u>

1.38



VIV3573S is a pendant linear profile made of extruded aluminum housing with a silver anodized finish, capped with a square frosted lens that surrounds the LED housing.

This linear luminaire is designed to produce a uniform distribution of diffused light in pendant applications. VIV3573S is secured using suspension wire ropes and comes in variable lengths up to 8 feet.*

Vivid series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. VIV3573S is a perfect fit for use in residential and commercial spaces for damp and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.

SPECIFIC

ELECTRICAL

WATTAGE

5W/ft, 10W/ft 24 Volt DC input

OPERATING TEMP

-31°F to +113°F

-35°C to +45°C

CERTIFICATION

USA and Canada UL safety approved



CONTROL

2.89"

DIMMING MODE

Class 2 Flicker-Free Dimmable, DMX Tunable, Non-Dimmable

WALL KEYPAD

Dimmer switch, Multi-zone DMX dim and tuning touch key with smart mobile App

PHYSICAL

DIMENSION

1.38 in x 2.89 in, 35x73mm Up to 8ft length, 0.79 lb/ft

FINISH

Silver anodized, Black matte, White matte*

FIELD

Suspended in damp or dry locations



LIGHT

LED TYPE

Single white, Tunable white, RGBW, Circadian Rhythm

EFFICACY

100 Lm/W, Max 800 Lm/ft *

LIFESPAN

50,000 hours

WARRANTY

5 years warranty

| VIV3573S | 8F | | 800 | | SA | | 30K | | JT | | F2 | |
|---------------------|------------------------|-----|-----------------|----|-----------------|------|-----------------------------|----|---------------------|----|------------|--|
| Pendant with Square | 1FT-8FT 1' to 8 | 400 | 400lm/ft 5W/ft | SA | Silver Anodized | 27K | 2700K Incandescent 90CRI | JT | Triac Phase Dimming | F2 | Dry Field | |
| Frosted Lens | Custom length up to 8 | 800 | 800lm/ft 10W/ft | BM | Black Matte | 30K | 3000K Warm Halogen 90CRI | JX | DMX Multi-Channel | F3 | Damp Field | |
| | | | | WM | White Matte | 35K | 3500K Neutral White 90CRI | JN | Non-Dimmable | | | |
| | | | | | | 40K | 4000K Cool White 90CRI | JD | DALI Dimmable | | | |
| | | | | | | 50K | 5000K Daylight White 90CRI | | | | | |
| | | | | | | 27T | 2700K-6500 Tunable 90CRI | | | | | |
| | | | | | | RGBW | RGB and 6500K White 90CRI | | | | | |
| | | | | | | CR | Circadian Rhythm 97R9 98CRI | | | | | |