



VIV5036F is a pendant-surface linear profile made of extruded aluminum housing with a protective silver anodized finish, capped with a flush frosted lens.

This linear LED luminaire is designed to produce a uniform distribution of diffused light in pendant or surface mounted applications. VIV5036F is secured on a surface using mounting clips or suspension wire ropes and can be used with connectors to attach multiple channels together. Connectors are available to form 90° angle, T-shape, cross, and linear extensions to enable creation of unique linear patterns. This channel comes in variable lengths up to 8 feet.\*

Vivid series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. VIV5036F is a perfect fit for use in residential and commercial spaces for damp and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.

SPECIFICATIONS

**ELECTRICAL**

**WATTAGE**

10W/ft, 15W/ft  
24 Volt DC input

**OPERATING TEMP**

-31°F to +113°F  
-35°C to +45°C

**CERTIFICATION**

USA and Canada UL  
safety approved



**CONTROL**

**DIMMING MODE**

Class 2 Flicker-Free  
Dimmable, DMX Tunable,  
Non-Dimmable

**WALL KEYPAD**

Dimmer switch, Multi-zone  
DMX dim and tuning touch  
key with smart mobile App

**PHYSICAL**

**DIMENSION**

1.97 in x 1.38 in, 50x35mm  
Up to 8ft length, 0.5 lb/ft

**FINISH**

Silver anodized, Black  
matte, White matte \*

**FIELD**

Pendant or surface in damp  
or dry wall and ceiling



**LIGHT**

**LED TYPE**

Single white, Tunable white,  
RGBW, Circadian Rhythm

**EFFICACY**

100 Lm/W, Max 1200 Lm/ft \*

**LIFESPAN**

50,000 hours

**WARRANTY**

5 years warranty

VIV5036F	8F	800	SA	30K	JT	F2
2" Wide Lens Pendant Linear Light	<b>1FT-8FT</b> 1' to 8' Custom length up to 8'	<b>800</b> 800lm/ft 10W/ft <b>1200</b> 1200lm/ft 15W/ft	<b>SA</b> Silver Anodized <b>BM</b> Black Matte <b>WM</b> White Matte	<b>27K</b> 2700K Incandescent 90CRI <b>30K</b> 3000K Warm Halogen 90CRI <b>35K</b> 3500K Neutral White 90CRI <b>40K</b> 4000K Cool White 90CRI <b>50K</b> 5000K Daylight White 90CRI <b>27T</b> 2700K-6500 Tunable 90CRI <b>RGBW</b> RGB and 6500K White 90CRI <b>CR</b> Circadian Rhythm 97R9 98CRI	<b>JT</b> Triac Phase Dimming <b>JX</b> DMX Multi-Channel <b>JN</b> Non-Dimmable <b>JD</b> DALI Dimmable	<b>F2</b> Dry Field <b>F3</b> Damp Field

\* Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details.  
Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.