



VIV5550S is a pendant linear light made of extruded aluminum housing with a protective silver anodized finish, capped with a square frosted lens that surrounds the LED housing.

This linear luminaire is designed to produce a bright uniform distribution of diffused light in pendant or surface mounted applications. VIV5550S is secured using suspension wire ropes and comes in variable lengths up to 8 feet.\*

Vivid series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. VIV5550S is a perfect fit for use in residential and commercial spaces for damp and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.

SPECIFICATIONS

**ELECTRICAL**

**WATTAGE**

10W/ft, 20W/ft  
24 Volt DC input

**OPERATING TEMP**

-31°F to +113°F  
-35°C to +45°C

**CERTIFICATION**

USA and Canada UL safety approved



**CONTROL**

**DIMMING MODE**

Class 2 Flicker-Free  
Dimmable, DMX Tunable,  
Non-Dimmable

**WALL KEYPAD**

Dimmer switch, Multi-zone  
DMX dim and tuning touch  
key with smart mobile App

**PHYSICAL**

**DIMENSION**

2.17 in x 1.97 in, 55x50mm  
Up to 8ft length, 0.79 lb/ft

**FINISH**

Silver anodized, Black  
matte, White matte \*

**FIELD**

Suspended in damp or dry  
locations



**LIGHT**

**LED TYPE**

Single white, Tunable white,  
RGBW, Circadian Rhythm

**EFFICACY**

100 Lm/W, Max 1600 Lm/ft \*

**LIFESPAN**

50,000 hours

**WARRANTY**

5 years warranty

VIV5550S	8F	800	SA	30K	JT	F2
Super Bright Suspended Linear Light	<b>1FT-8FT</b> 1' to 8' Custom length up to 8'	<b>800</b> 800lm/ft 10W/ft <b>1600</b> 1600lm/ft 20W/ft	<b>SA</b> Silver Anodized <b>BM</b> Black Matte <b>WM</b> White Matte	<b>27K</b> 2700K Incandescent 90CRI <b>30K</b> 3000K Warm Halogen 90CRI <b>35K</b> 3500K Neutral White 90CRI <b>40K</b> 4000K Cool White 90CRI <b>50K</b> 5000K Daylight White 90CRI <b>27T</b> 2700K-6500 Tunable 90CRI <b>RGBW</b> RGB and 6500K White 90CRI <b>CR</b> Circadian Rhythm 97R9 98CRI	<b>JT</b> Triac Phase Dimming <b>JX</b> DMX Multi-Channel <b>JN</b> Non-Dimmable <b>JD</b> DALI Dimmable	<b>F2</b> Dry Field <b>F3</b> Damp Field

\* Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details.  
Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.