



VIV7676F is a pendant linear profile made of extruded aluminum housing with a protective silver anodized finish, capped with a flush frosted lens.

This linear LED luminaire is designed with a wide construct to produce a bright uniform distribution of diffused light in pendant applications. VIV7676F is secured using suspension wire ropes and comes in variable lengths up to 8 feet. *

Vivid series are complemented with dimmable, energy-efficient, dot-free LED, producing high color rendering index lighting. The bright white LED light source with CCT options from 2200K to 6000K provides the environment with desired lighting that fits the design concept.

The lighting system can be conveniently controlled with wall remote, hand remote, and smart app options. VIV7676F is a perfect fit for use in residential and commercial spaces for damp and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.

SPECIFICATIONS

ELECTRICAL

Input
24 V - 20 W/ft - 64 W/m

Power Supply
Class 2 Dimmable 20KHZ
Lutron Hi-lume 0.1%
Lutron 3-wire 100%-1%

Operating temp
- 31°F to + 113°F
- 35°C to + 45°C

Certification
USA and Canada UL
safety approved



CONTROL

Options
Combination of wireless wall touch keys, portable remotes, and mobile App

Range
Wireless controlling transmits RF in 30m range

Multi-zone
Individual and collective zone options for color and brightness control

Dimming
Brightness, color tuning, & light mode with memory saving options

PHYSICAL

Dimension
2.99 in x 2.99 in - 76x76mm
Up to 8 ft (2.5 m) length *
1.28 lbs/ft - 1.9 kg/m

Finish
Silver anodized aluminium, black, or white finish *

Field
Damp and dry applications

Mounting
Pendant via variable-length suspension wire ropes



LIGHT

LED type
Single and tunable white, Circadian BIOS SkyBlue

CCT
3000K 3500K 4000K
4500K 5000K 5500K *

CRI
High CRI up to 97 *

Brightness
1600 Lm/ft - 5600 Lm/m *

Life time
50,000 hours

Warranty
5 years warranty

* AVAILABLE FOR CUSTOM APPLICATIONS. VISIT ENOLIGHT.COM OR CONTACT SALES@ENOLIGHT.COM +1 833 366 5444 FOR FURTHER DETAILS. DISCLAIMER: THE ACTUAL PRODUCT MAY VARY FROM THE IMAGES SHOWN. DUE TO DIFFERENCES IN MONITORS, COLOURS OF PRODUCTS MAY ALSO APPEAR DIFFERENT TO THOSE SHOWN. SPECIFICATION AND ILLUSTRATIONS PROVIDED FOR EACH PRODUCT IS TO BE USED AS A GENERAL GUIDE ONLY. COPYRIGHT © 2017-2019 ENOLIGHT LTD. ALL RIGHTS RESERVED.