



SPK13350F is a recessed linear profile made of extruded aluminum housing with a protective silver anodized finish, capped with a flush frosted lens.

This linear luminaire is designed to produce an indirect uniform distribution of light in drywall platforms. SPK13350F is suitable for ceiling cove lighting and comes in variable lengths up to 8 feet.*

Spark series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. SPK13350F is a perfect fit for use in residential and commercial spaces for wet and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



SPECIFICATIONS

ELECTRICAL

WATTAGE

5W/ft, 10W/ft
24 Volt DC input

OPERATING TEMP

-31°F to +113°F
-35°C to +45°C

CERTIFICATION

U.S./Canada UL approved
Type IC Recessed



CONTROL

DIMMING MODE

Class 2 Flicker-Free
Dimmable, DMX Tunable,
Non-Dimmable

WALL KEYPAD

Dimmer switch, Multi-zone
DMX dim and tuning touch
key with smart mobile App

PHYSICAL

DIMENSION

5.24 in x 2.01 in, 133x51mm
Up to 8ft length, 0.58 lb/ft

FINISH

Silver anodized, Black matte,
White matte *

FIELD

Recessed in damp or dry
ceiling and wall areas



LIGHT

LED TYPE

Single white, Tunable white,
RGBW, Circadian Rhythm

EFFICACY

100 Lm/W, Max 800 Lm/ft *

LIFESPAN

50,000 hours

WARRANTY

5 years warranty

SPK13350F

8F

400

MF

30K

JT

F2

Drywall Ceiling Indirect
Cove Linear Light

1FT-8FT 1' to 8'
Custom length up to 8'

400 400lm/ft 5W/ft
800 800lm/ft 10W/ft

SA Silver Anodized
BM Black Matte
WM White Matte

27K 2700K Incandescent 90CRI
30K 3000K Warm Halogen 90CRI
35K 3500K Neutral White 90CRI
40K 4000K Cool White 90CRI
50K 5000K Daylight White 90CRI
27T 2700K-6500 Tunable 90CRI
RGBW RGB and 6500K White 90CRI
CR Circadian Rhythm 97R9 98CRI

JT Triac Phase Dimming
JX DMX Multi-Channel
JN Non-Dimmable
JD DALI Dimmable

F2 Dry Field
F3 Damp Field

* Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details.
Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.