



SPK7515F is a recessed linear profile made of extruded aluminum housing with a protective white sand texture powder coat matte finish, capped with a flush frosted lens.

This linear luminaire is designed to produce a uniform distribution of diffused light in drywall platforms. SPK7515F is suitable for wall and ceiling linear light designs and comes in variable lengths up to 18 feet.\*

Spark series can be conveniently controlled with multi-zone wall touch keypad and smart mobile app options. SPK7515F is a perfect fit for use in residential and commercial spaces for wet and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



**ELECTRICAL**

**WATTAGE**

2.4W/ft, 5W/ft, 10W/ft  
24 Volt DC input

**OPERATING TEMP**

-31°F to +113°F  
-35°C to +45°C

**CERTIFICATION**

U.S./Canada UL approved  
Type IC Recessed



**CONTROL**

**DIMMING MODE**

Class 2 Flicker-Free  
Dimmable, DMX Tunable,  
Non-Dimmable

**WALL KEYPAD**

Dimmer switch, Multi-zone  
DMX dim and tuning touch  
key with smart mobile App

**PHYSICAL**

**DIMENSION**

2.98 in x 0.58 in, 76x15mm  
Up to 18ft length, 0.35 lb/ft

**FINISH**

Silver anodized, Black matte,  
White matte \*

**FIELD**

Recessed in wet or dry  
ceiling and wall areas



**LIGHT**

**LED TYPE**

Single white, Tunable white,  
RGBW, Circadian Rhythm

**EFFICACY**

100 Lm/W, Max 800 Lm/ft \*

**LIFESPAN**

50,000 hours

**WARRANTY**

5 years warranty

SPK7515F	12F	400	MF	30K	JT	F2
1 Inch Drywall Linear LED Light	<b>1FT-18FT</b> 1' to 18' Custom length up to 18'	<b>200</b> 200lm/ft 2.4W/ft <b>400</b> 400lm/ft 5W/ft <b>800</b> 800lm/ft 10W/ft	<b>SA</b> Silver Anodized <b>BM</b> Black Matte <b>WM</b> White Matte <b>MF</b> Mill Finish	<b>27K</b> 2700K Incandescent 90CRI <b>30K</b> 3000K Warm Halogen 90CRI <b>35K</b> 3500K Neutral White 90CRI <b>40K</b> 4000K Cool White 90CRI <b>50K</b> 5000K Daylight White 90CRI <b>27T</b> 2700K-6500 Tunable 90CRI <b>RGBW</b> RGB and 6500K White 90CRI <b>CR</b> Circadian Rhythm 97R9 98CRI	<b>JT</b> Triac Phase Dimming <b>JX</b> DMX Multi-Channel <b>JN</b> Non-Dimmable <b>JD</b> DALI Dimmable	<b>F2</b> Dry Field <b>F5</b> Wet Field

\* Available for custom applications. Visit enolight.com or contact sales@enolight.com for further details.  
Disclaimer: The actual product may vary from the images shown. Due to differences in monitors, colours of products may also appear different to those shown. Specification and illustrations provided for each product is to be used as a general guide only. Copyright © EnoLight Ltd. All Rights Reserved.