



VIV3535F is a pendant-surface linear profile made of extruded aluminum housing with a protective silver anodized finish, capped with a flush frosted lens.

This linear LED luminaire is designed to produce a uniform distribution of diffused light in pendant or surface mounted applications. VIV3535F is secured on a surface using mounting clips or suspension wire ropes and can be used with connectors to attach multiple channels together. Connectors are available to form 90° angle, T-shape, cross, and linear extensions to enable creation of unique linear patterns. This channel comes in variable lengths up to 8 feet. *

Vivid series are complemented with dimmable, energy-efficient, dot-free LED, producing high color rendering index lighting. The bright white LED light source with CCT options from 2200K to 6000K provides the environment with desired lighting that fits the design concept.

The lighting system can be conveniently controlled with wall remote, hand remote, and smart app options. VIV3535F is a perfect fit for use in residential and commercial spaces for damp and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years limited warranty.

SPECIFICATIONS

ELECTRICAL

- Input**
24 V - 10 W/ft - 32 W/m
- Power Supply**
Class 2 Dimmable 20KHZ
Lutron Hi-lume 0.1%
Lutron 3-wire 100%-1%
- Operating temp**
- 31°F to + 113°F
- 35°C to + 45°C
- Certification**
USA and Canada UL
safety approved



CONTROL

- Options**
Combination of wireless wall touch keys, portable remotes, and mobile App
- Range**
Wireless controlling transmits RF in 30m range
- Multi-zone**
Individual and collective zone options for color and brightness control
- Dimming**
Brightness, color tuning, & light mode with memory saving options

PHYSICAL

- Dimension**
1.38 in x 1.38 in - 35x35 mm
Up to 8 ft (2.5 m) length *
0.44 lbs/ft - 0.65 kg/m
- Finish**
Silver anodized aluminium, black, or white finish *
- Field**
Damp and dry applications
- Mounting**
Pendant or surface with 4 connector options



LIGHT

- LED type**
Single and tunable white, Circadian BIOS SkyBlue
- CCT**
3000K 3500K 4000K
4500K 5000K 5500K *
- CRI**
High CRI up to 97 *
- Brightness**
800 Lm/ft - 2800 Lm/m *
- Life time**
50,000 hours
- Warranty**
5 years warranty

* AVAILABLE FOR CUSTOM APPLICATIONS. VISIT ENOLIGHT.COM OR CONTACT SALES@ENOLIGHT.COM +1 833 366 5444 FOR FURTHER DETAILS. DISCLAIMER: THE ACTUAL PRODUCT MAY VARY FROM THE IMAGES SHOWN. DUE TO DIFFERENCES IN MONITORS, COLOURS OF PRODUCTS MAY ALSO APPEAR DIFFERENT TO THOSE SHOWN. SPECIFICATION AND ILLUSTRATIONS PROVIDED FOR EACH PRODUCT IS TO BE USED AS A GENERAL GUIDE ONLY. COPYRIGHT © 2017-2019 ENOLIGHT LTD. ALL RIGHTS RESERVED.