# RECESSED MOUNT CABINET CLOSET LINEAR LIGHT



0.28

#### HYN1208F is a recessed light made of extruded aluminum housing, capped with a flush matte premium frosted lens.

HYPHEN SERIES

YN1208F

This linear LED luminaire is designed to produce a uniform distribution of diffused light in wooden platforms. HYN1208F has a narrow base and is suitable for closet, under cabinet, stair nosing and wall unit linear light designs. This channel comes in variable lengths up to 10 feet. \*

Hyphen series are complemented with dimmable, energy-efficient, dot-free LED, producing high color rendering index lighting. The bright white LED light source with CCT options from 2200K to 6000K provides the environment with desired lighting that fits the design concept.

The lighting system can be conveniently controlled with wall remote, hand remote, and smart app options. HYN1208F is a perfect fit for use in residential and commercial to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.

## **ELECTRICAL**

#### Input

24 V - 2.4 W/ft - 8 W/m

#### **Power Supply**

SPECIFICATIONS

Class 2 Dimmable 20KHZ Lutron Hi-lume 0.1% Lutron 3-wire 100%-1%

#### **Operating temp**

- 31°F to + 113°F - 35°C to + 45°C

## Certification U.S./Canada UL approved

Type IC Recessed



## CONTROL

Tile/Wood

0.47"

## Options

Combination of wireless wall touch keys, portable remotes, and mobile App

Range Wireless controlling transmits RF in 30m range

#### Multi-zone

Individual and collective zone options for color and brightness control

#### Dimming

Brightness, color tuning, & light mode with memory saving options

Dimension

PHYSICAL

## 0.47 in x 0.28 in - 12x7mm Up to 10 ft (3 m) length \* 0.05 lbs/ft - 0.07 kg/m

Finish Mill, black, white, Silver anodized finish \*

#### Field Indoor dry applications

Mounting

## Recessed under cabinet or wooden platforms



## LIGHT

## LED type

Single and tunable white, Circadian BIOS SkyBlue

#### CCT

3000K 3500K 4000K 4500K 5000K 5500K \* CRI

High CRI up to 97 \*

## **Brighness**

200 Lm/ft - 700 Lm/m \* Life time

50,000 hours

Warrantv 5 years warranty

