



HYN1910F is a waterproof recessed linear profile made of extruded aluminum with a protective silver anodized finish, supported with a frosted lens housing.

This linear LED luminaire is designed to produce a uniform distribution of diffused light in outdoor tiles and interlocks. HYN1910F has a waterproof construct and is suitable for light designs applied in submerged or wet in-ground environments such as landscape and pool lighting. This channel comes in variable lengths up to 8 feet. *

Hyphen series are complemented with dimmable, energy-efficient, dot-free LED, producing high color rendering index lighting. The bright white LED light source with CCT options from 2200K to 6000K provides the environment with desired lighting that fits the design concept.

The lighting system can be conveniently controlled with wall remote, hand remote, and smart app options. HYN1910F is a perfect fit for use in outdoor applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



SPECIFICATIONS

ELECTRICAL

Input

24 V - 5 W/ft - 16 W/m

Power Supply

Class 2 Dimmable 20KHZ
Lutron Hi-lume 0.1%
Lutron 3-wire 100%-1%

Operating temp

- 31°F to + 113°F
- 35°C to + 45°C

Certification

U.S./Canada UL approved
Type IC Recessed



CONTROL

Options

Combination of wireless wall touch keys, portable remotes, and mobile App

Range

Wireless controlling transmits RF in 30m range

Multi-zone

Individual and collective zone options for color and brightness control

Dimming

Brightness, color tuning, & light mode with memory saving options

PHYSICAL

Dimension

0.75 in x 0.39 in - 19x10 mm
Up to 8 ft (2.5 m) length *
0.13 lbs/ft - 0.2 kg/m

Finish

Sliver anodized, black, or white aluminium finish *

Field

In-ground outdoor IP68

Mounting

Recessed in tile and stone wet areas



LIGHT

LED type

Single and tunable white, Circadian BIOS SkyBlue

CCT

3000K 3500K 4000K
4500K 5000K 5500K *

CRI

High CRI up to 97 *

Brightness

400 Lm/ft - 1400 Lm/m *

Life time

50,000 hours

Warranty

5 years warranty