



STP6728F is a linear stair-nosing profile made of extruded aluminum housing with a protective silver anodized finish. The light channel projects upward and is capped with a flush frosted lens.

This linear LED luminaire is designed to produce a uniform distribution of diffused light in stair applications. STP6728F has an anti-slip stair nosing construct and comes in variable lengths up to 8 feet. \*

Step series are complemented with energy-efficient, dot-free, dimmable LED, producing high color rendering index lighting. The bright white LED light source with CCT options from 2200K to 6000K provides the environment with desired lighting that fits the design concept.

The lighting system can be conveniently controlled with wall remote, hand remote, and smart app options. STP6728F is a perfect fit for use in residential and commercial spaces for damp and dry applications to produce ambient or decorative illumination.

EnoLight lighting solutions are designed and manufactured in Canada to the highest industry standards with 5 years warranty.



**SPECIFICATIONS**

**ELECTRICAL**

**Input**

24 V - 5 W/ft - 16 W/m

**Power Supply**

Class 2 Dimmable 20KHZ  
Lutron Hi-lume 0.1%  
Lutron 3-wire 100%-1%

**Operating temp**

- 31°F to + 113°F  
- 35°C to + 45°C

**Certification**

U.S./Canada UL approved  
Type IC Recessed



**CONTROL**

**Options**

Combination of wireless wall touch keys, portable remotes, and mobile App

**Range**

Wireless controlling transmits RF in 30m range

**Multi-zone**

Individual and collective zone options for color and brightness control

**Dimming**

Brightness, color tuning, & light mode with memory saving options

**PHYSICAL**

**Dimension**

2.65 in x 1.1 in - 67x28 mm  
Up to 8 ft (2.5 m) length \*  
0.47 lbs/ft - 0.7 kg/m

**Finish**

Silver anodized aluminium, black, or white finish \*

**Field**

Damp and dry applications

**Mounting**

Surface-mounted on stair tread nosing



**LIGHT**

**LED type**

Single and tunable white, Circadian BIOS SkyBlue

**CCT**

3000K 3500K 4000K  
4500K 5000K 5500K \*

**CRI**

High CRI up to 97 \*

**Brightness**

400 Lm/ft - 1400 Lm/m \*

**Life time**

50,000 hours

**Warranty**

5 years warranty